



**INDIA'S ONLY TRUSTED GOVERNMENT-APPROVED, PATENTED & LICENSED
BRAND SPECIALIZING IN AIR QUALITY AND HUMIDITY SOLUTIONS**

The Most Preferred Brand on the Government e-Marketplace (GeM) Portal



A Group Company of AMFAH GENERAL TRADING LLC, Dubai

We Make Air Quality and Humidity Control Easy

In collaboration with leading technology partners worldwide

AMFAH INDUSTRIAL DEHUMIDIFIER WITH AIR PURIFICATION

AMF 138 DMP

- High-Capacity Extraction: Up to 138 Liters/Day (at 35°C / 90% RH) and 100 Liters/Day at high temperatures
- Wide Coverage Area: Recommended for spaces up to 14,000 cu. ft. (397 cu. mt.)
- Focused Drying: Ductable option allows the air outlet to be connected to ducting for targeted drying
- Smart Controls: LED Display and electronic controls for precise humidity management
- Integrated Condensate Pump: High-lift water pump dispenses condensate vertically/horizontally up to 15 feet



Widely Used In:

Health Care Facilities, Hospitals & Clinics, Testing Laboratories, Hotels & Restaurants, Art Galleries & Boutiques, Printing Industries, Equipment & Console Rooms, Libraries & Archives, Food Industry, Packing Industry, Pharmaceutical Industry, Data & Server Rooms, Warehouse & Storage Facilities & Many More...

AMFAH INDUSTRIAL DEHUMIDIFIER WITH AIR PURIFICATION

AMF 138 DMP

Technical Specification	
Model Name	AMF 138 DMP
Rated Voltage / Frequency	220V / 50Hz
Normal Dehumidification Capacity (27°C/60%RH)	2.5 kg/h
High Temp. Dehumidification Capacity	100 L/d
Max Dehumidification Capacity (35°C/90%RH)	138 L/d
Nominal Power (27°C/60%RH)	1300 W
Power (30°C/80%RH)	1550 W
Max Power (35°C/90%RH)	1800 W
Max Current (35°C/90%RH)	8.5 A
Air Volume	1100 m ³ /h
Refrigerant / Injection Amount	R410A / 730 g
Body Size (L x W x H)	18.898 × 17.126 × 37.008 inches
Weight	48 kg
Water Tank	14 L
Noise Level (Low / High)	62 dB / 68 dB



: +91 9321991812



:+91 9004663226/9324516326



www.amfah.com



info.india@amfah.com